

IN THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the present application:

1-20. (Canceled)

21. (Currently amended) A device to log information in a network cache, the device comprising:

an application module to receive requests from a plurality of clients for content maintained by an origin server and to receive responses to the requests from the origin server;

an interface to allow selection of a protocol, selection for logging of some or all of a plurality of fields of the protocol that may be present in each of said requests and responses ~~a message to be received~~, and specification of a sequence in which the selected fields are to appear in a log file; and

a log module to record information of the received requests and responses into the log file, according to the selected protocol, the selected fields of the protocol, and the specified sequence.

~~a first data structure for storing a value indicating a position in the specified sequence for each selected field;~~

~~— a protocol independent log module to receive information from an application module, to store the information in a second data structure, and to store a reference to the information for each selected field stored in the second data structure in a location~~

~~of a third data structure that corresponds to the position in the specified sequence for the corresponding field; and~~

~~—— a log file wherein the information for each selected field from the second data structure is sequentially written using the reference from the third data structure.~~

22. (Canceled)

23. (Previously presented) The device of claim 21, wherein the interface allows the creation of new fields in addition to the plurality of fields.

24. (Canceled)

25. (Previously presented) The device of claim 21, wherein the interface is a graphical user interface.

26. (Previously presented) The device of claim 21, wherein the interface is a command line interface.

27. (Currently amended) A method of logging information in a network cache, the method comprising:

receiving requests from a plurality of clients for content maintained by an origin server;

receiving responses to said requests from the origin server;

providing receiving inputs via an interface to allow make selection for logging of some or all of a plurality of fields that may be present in each of said requests and

~~responses a message to be received~~ and to make specification of a sequence in which the selected fields are to appear in a log file;

storing in a first data structure a value indicating the position in the specified sequence of each selected field;

in response to receiving each of the requests and responses ~~a message received over a network from a remote node,~~

obtaining information for each selected field associated with the ~~message~~ corresponding request or response and storing the information in a second data structure, in a sequence independent of the specified sequence,

storing in a third data structure, based on the first data structure, a reference to the information for each selected field stored in the second data structure, including storing each reference in a location of the third data structure that corresponds to the position in the specified sequence of the corresponding field; and

using the third data structure to output the information for each selected field in the second data structure to ~~[[a]]~~ the log file, such that the information for each selected field appears in the log file according to the specified sequence.

28. (Previously presented) The method of claim 27, wherein the interface allows creation of new fields in addition to the plurality of fields.

29. (Previously presented) The method of claim 27, wherein the information for each field is converted to an ASCII representation and is of variable length.

30. (Previously presented) The method of claim 27, wherein each location in the first data structure is pre-initialized to contain a flag before the specified sequence is stored, the flag to be utilized as an indicator that the corresponding field was not selected for logging.

31. (Currently amended) The method of claim 27, wherein the second data structure and the third data structure are created to respond to logging for the ~~message~~ corresponding request or response and destroyed once logging for the ~~message~~ corresponding request or response is completed.

32. (Currently amended) The method of claim 27, wherein the first data structure persists through logging for the requests and responses ~~a plurality of messages received from remote nodes~~.

33. (Previously presented) The method of claim 27, wherein using the third data structure to output the information further comprises sequentially accessing the third data structure to read the position of the information corresponding to each selected field and accessing the second data structure to read information corresponding to each selected field at the position indicated by the reference.

34. (Currently amended) A device for logging information in a network cache, the network cache serving a plurality of clients on behalf of an origin server, the device comprising:

an interface to allow selection of a protocol, selection for logging of some or all of a plurality of fields of a message to be received from anyone of the origin server and the

plurality of clients, the fields corresponding to the selected protocol, and specification of a sequence in which the selected fields are to appear in a log file of the network cache, wherein the interface further allows changing said selections to modify the log file's format while the network cache is running;

a protocol specific application module to obtain information for each selected field associated with the message;

a protocol independent log module to receive information for each selected field from the protocol specific application module and to store the information for each selected field in [[a]] the log file in the sequence specified.

35. (Canceled)

36. (Previously presented) The device of claim 36, wherein the interface allows creation of new fields in addition to the plurality of fields.

37. (Canceled)

38. (Previously presented) The device of claim 36, wherein the interface is a graphical user interface.

39. (Previously presented) The device of claim 36, wherein the interface is a command line interface.

40-45. (Canceled)

46. (New) The device of claim 21, wherein the interface further allows changing said selections to modify the log file's format while the network cache is running.

47. (New) The method of claim 27, wherein the interface allows changing the selection and the sequence to modify the log file's format while the network cache is running.

48. (New) A method of operating a network cache, the method comprising:
receiving requests from a plurality of clients for contents maintained by a server and responses to the requests from the server, wherein the requests and responses are formatted according to a protocol;

receiving selection of a first number of fields from a plurality of fields of the protocol that may be present in each of the requests and responses, and receiving specification of a first sequence in which the first number of fields are to appear in a log file of the network cache;

recording the first number of fields extracted from a first one of the requests and responses into the log file according to the first sequence;

while operating the network cache,

receiving inputs that changes selection of fields from the first number of fields to a second number of fields and specifies a second sequence;

recording the second number of fields extracted from a second one of the requests and responses into the log file according to the second sequence.

49. (New) The method of claim 48, wherein recording the first number of fields extracted from a first one of the requests and responses into the log file according to the first sequence comprises

storing in a first data structure a value indicating the position in the first sequence of each of the first number of fields;

obtaining information for each of the first number of fields associated with the first one of requests and responses and storing the information in a second data structure, in a sequence independent of the first sequence,

storing in a third data structure, based on the first data structure, a reference to the information for each of the first number of fields stored in the second data structure, including storing each reference in a location of the third data structure that corresponds to the position in the first sequence of the corresponding field; and

using the third data structure to output the information for each of the first number of fields in the second data structure to the log file, such that the information for each of the first number of fields appears in the log file according to the first sequence.